



**ME & WE**  
mwpcdtools.com

**ME&WE**  
**DIAMOND GRINDING WHEEL**  
Super Wear-Resistance



**ME&WE**  
**PDC DRILL BIT**  
Longer Drilling Footage



## ND Tin Coating Wire Drawing Dies Pcd Drawing Dies 0.04mm To 0.299mm

### Our Product Introduction

#### Basic Information

- Place of Origin: China
- Model Number: ND Tin Coating Dies
- Minimum Order Quantity: 1 Piece
- Price: Negotiable
- Packaging Details: Carton, Box
- Delivery Time: 5-10 work days
- Payment Terms: T/T, L/C, Western Union
- Supply Ability: 200 pieces per day



#### Product Specification

- Wire Drawing Dies: ND Tin Coating Dies
- Material: Natural Diamond
- Size: Customized Size
- Application: Wire Drawing Industry
- Mold Life: 1-2 Years
- Transport: By Air
- Highlight: **ND Tin Coating Wire Drawing Dies, Wire Drawing Dies 0.04mm, pcd drawing dies 0.299mm**

for more products please visit us on [mwpcdtools.com](http://mwpcdtools.com)

## Product Description

### ND Tin Coating Dies, Wire Drawing Dies

#### 1. Description:

ND (Natural Diamond) Tin Coating Dies are available. Each blank of the Tin Coating Die is selected strictly to ensure there are no crack and impurities. Advanced machines and complete production processes make the Tin Coating Dies to be accurate, consistent.

#### 2. Specifications:

Available Sizes: 0.04mm~0.299 mm

| inches        | mm           | ADDMA | Maximum Diameter |
|---------------|--------------|-------|------------------|
| 0.0039-0.0157 | 0.100-0.400  | D6    | 0.4              |
| 0.0079-0.0315 | 0.200-0.800  | D12   | 0.8              |
| 0.0079-0.0394 | 0.200-1.000  | D12   | 1.0              |
| 0.0197-0.0591 | 0.500-1.500  | D15   | 1.5              |
| 0.0197-0.0591 | 0.500-1.500  | D15   | 1.5              |
| 0.0315-0.0787 | 0.800-2.000  | D18   | 2.0              |
| 0.0315-0.0787 | 0.800-2.000  | D18   | 2.0              |
| 0.0472-0.1181 | 1.200-3.100  | D21   | 3.1              |
| 0.0472-0.1181 | 1.200-3.100  | D21   | 3.1              |
| 0.0591-0.1732 | 1.500-4.400  | D24   | 4.4              |
| 0.0591-0.1732 | 2.000-4.400  | D24   | 4.4              |
| 0.1299-0.2126 | 3.300-5.400  | D27   | 5.4              |
| 0.1299-0.2183 | 3.300-5.800  | D27   | 5.8              |
| 0.2008-0.2992 | 5.100-7.600  | D30   | 7.6              |
| 0.3150-0.4331 | 8.000-11.000 | D33   | 11.0             |
| 0.3150-0.4409 | 8.000-11.200 | D30   | 11.2             |
| 0.3150-0.4724 | 8.000-12.000 | D33   | 12.0             |
| 0.3150-0.4921 | 8.000-12.500 | D33   | 12.5             |
| 0.3150-0.5000 | 8.000-12.700 | D36   | 12.7             |

#### 3. Application:

Tin Coating Dies' special titanium casing make the dies float on the tin solution and then finish the tin coating process. And the big die exit make the tin solution not stain on the casing.

#### 4. Advantage:

Long life time, good tin coating effect and predictable wire surface.



ME & WE



18837137981



zyxelina@sina.com



[mwpcdtools.com](http://mwpcdtools.com)