



**ME & WE**  
mwpcdtools.com

**ME&WE**  
**DIAMOND GRINDING WHEEL**  
Super Wear-Resistance +



**ME&WE**  
**PDC DRILL BIT**  
Longer Drilling Footage +



## D36 PCD Drawing Dies 8mm To 12.7mm Diamond Dies For Wire Drawing

Our Product Introduction

### Basic Information

- Place of Origin: China
- Model Number: D6 - D36
- Minimum Order Quantity: 1 Piece
- Price: Negotiable
- Packaging Details: Carton, Box
- Delivery Time: 5-10 work days
- Payment Terms: T/T, L/C, Western Union
- Supply Ability: 200 pieces per day



### Product Specification

- PCD Drawing Dies: Energy Industry
- Material: PCD Core
- Size: Customized Size
- Surface Treatment: Polishing
- Mold Life: 1-2 Years
- Transport: By Air
- Highlight: **D36 PCD Drawing Dies ,  
D36 PCD Drawing Dies 12.7mm ,  
8MM diamond dies for wire drawing**

for more products please visit us on [mwpcdtools.com](http://mwpcdtools.com)

## Product Description

### PCD Drawing Dies, Polycrystalline Diamond Dies, Wire Drawing Dies for Energy Industry

#### 1. Description:

Energy saving and consumption reduction in China which it's going to the forefront of the world's clean energy utilization, become the largest manufacturer and applications of solar photovoltaic power generation. Our Drawing dies in the field of photovoltaic cell wafer slicing plays a role that can not be ignored.

#### 2. Specifications:

| inches        | mm           | ADDMA | Maximum Diameter |
|---------------|--------------|-------|------------------|
| 0.0039-0.0157 | 0.100-0.400  | D6    | 0.4              |
| 0.0079-0.0315 | 0.200-0.800  | D12   | 0.8              |
| 0.0079-0.0394 | 0.200-1.000  | D12   | 1.0              |
| 0.0197-0.0591 | 0.500-1.500  | D15   | 1.5              |
| 0.0197-0.0591 | 0.500-1.500  | D15   | 1.5              |
| 0.0315-0.0787 | 0.800-2.000  | D18   | 2.0              |
| 0.0315-0.0787 | 0.800-2.000  | D18   | 2.0              |
| 0.0472-0.1181 | 1.200-3.100  | D21   | 3.1              |
| 0.0472-0.1181 | 1.200-3.100  | D21   | 3.1              |
| 0.0591-0.1732 | 1.500-4.400  | D24   | 4.4              |
| 0.0591-0.1732 | 2.000-4.400  | D24   | 4.4              |
| 0.1299-0.2126 | 3.300-5.400  | D27   | 5.4              |
| 0.1299-0.2183 | 3.300-5.800  | D27   | 5.8              |
| 0.2008-0.2992 | 5.100-7.600  | D30   | 7.6              |
| 0.3150-0.4331 | 8.000-11.000 | D33   | 11.0             |
| 0.3150-0.4409 | 8.000-11.200 | D30   | 11.2             |
| 0.3150-0.4724 | 8.000-12.000 | D33   | 12.0             |
| 0.3150-0.4921 | 8.000-12.500 | D33   | 12.5             |
| 0.3150-0.5000 | 8.000-12.700 | D36   | 12.7             |

Note: The above hole sizes are recommended for soft wire. In case of hard wire drawing, the maximum hole size should not exceed 65% of them.

#### 3. Application:

It is used for Energy Industry.

#### 4. Advantage:

Longest die life of any die material, Highest production efficiency with less downtime and predictable surface finish of wire.



ME & WE



18837137981



zyxelina@sina.com



[mwpcdttools.com](http://mwpcdttools.com)